

Samsung Security Solutions

Product Line-Up Catalog



SAMSUNG TECHWIN AMERICA



SRK-3040S	SRK-3030S	SRK-4060S	SRK-5120S	
4CH/4CAM	4CH/3CAM (w/5MP fisheye)	8CH/6CAM	16CH/12CAM	
<ul style="list-style-type: none"> • 1080p Full HD recording and display • Plug-n-Play with Setup Wizard • PoE+ switch built in NVR • ONVIF Camera Compliant • SND-L6013R (Qty 4), SRN-473S (NVR) 	<ul style="list-style-type: none"> • 5MP recording and display • Plug-n-Play with Setup Wizard • PoE+ switch built in NVR • Dewarped on camera 180/360 panoramic view • ONVIF Camera Compliant • SND-L6013R (Qty 2), SNF-8010 (Fisheye), SRN-473S (NVR) 	<ul style="list-style-type: none"> • 1080p Full HD recording and display • Plug-n-Play with Setup Wizard • PoE+ switch built in NVR • ONVIF Camera Compliant • SND-L6013R (Qty 6), SRN-873S (NVR) 	<ul style="list-style-type: none"> • 1080p Full HD recording and display • Plug-n-Play with Setup Wizard • PoE+ switch built in NVR • ONVIF Camera Compliant • SND-L6013R (Qty 12), SRN-1673S (NVR) 	
SNB-9000	5MP	SNB-8000	SNO-8081R	
4K UHD & 12MP Network		5MP Full HD	IK10 IP66	
<ul style="list-style-type: none"> • 12MP @ 20fps / 4K @ 30fps • Simple Focus • H.264, Day & Night (ICR) • Intelligent Video Analytics 		<ul style="list-style-type: none"> • 5MP @ 20fps, 1080p @ 30fps • Exceptional low light 0.01 Lux (1/20, 30IRE) • Simple Focus, P-Iris • Built-in Mic • Tampering, Audio Detection 	5MP Weatherproof IR <ul style="list-style-type: none"> • 30fps@all resolutions • Concurrent H.265 & H.264 Streaming • 0.1Lux@F1.2 (Color), 0Lux (B/W : IR LED on) • 2.4x motorized varifocal lens • Hallway view (Rotate 90° / 270°) • Lens Distortion Correction • IK10, IP66 	
SNV-8080	SNV-8081R	SNF-8010	SNF-8010VM	3MP
IK10 IP66	IK10 IP66	5MP 360° Fisheye	IK10 IP66	
5MP Vandal-Resistant	H.265 5MP Vandal-Resistant IR	5MP 360° Fisheye	5MP 360° Fisheye Mobile Vandal-Resistant	
<ul style="list-style-type: none"> • 5MP @ 20fps, 1080p @ 30fps • Exceptional low light 0.01 Lux (1/20, 30IRE) • Simple Focus • Heater by PoE (-40°F) • IK10, IP66 	<ul style="list-style-type: none"> • 30fps@all resolutions • 0.1Lux@F1.2 (Color), 0Lux (B/W : IR LED on) • 2.6x motorized varifocal lens • Hallway view (Rotate 90° / 270°) • Lens Distortion Correction • Concurrent H.265 & H.264 • IK10, IP66 	<ul style="list-style-type: none"> • 6 Dewarping View Modes • Digital PTZ / Bi-Directional Audio • Digital Wide Dynamic Range • Motion Detection 	<ul style="list-style-type: none"> • 6 Dewarping View Mode • Digital PTZ / Bi-Directional Audio • Digital Wide Dynamic Range • Motion Detection, Audio Detection • M12 & RJ-45 Connector • IK10, IP66 	
SNB-7004	SNO-7084R	SND-7084	SND-7084R	SNV-7084/7084R
WiseNet III	WiseNet III	WiseNet III	WiseNet III	WiseNet III
3MP Full HD	3MP Full HD Weatherproof IR	3MP Full HD	3MP Full HD IR	3MP Vandal-Resistant/IR
<ul style="list-style-type: none"> • 3MP @ 30fps • Wide Dynamic Range (120dB) • Simple focus, P-Iris • Day & Night (ICR), Digital Image Stabilization, Defog • IK10, IP66 	<ul style="list-style-type: none"> • 3MP @ 30fps • Wide Dynamic Range (120dB) • Simple focus, P-Iris • Day & Night (ICR), Digital Image Stabilization, Defog • IK10, IP66 	<ul style="list-style-type: none"> • 3MP @ 30fps • Wide Dynamic Range (120dB) • Simple focus, P-Iris • Day & Night (ICR), Digital Image Stabilization, Defog 	<ul style="list-style-type: none"> • 3MP @ 30fps • Wide Dynamic Range (120dB) • Simple focus, P-Iris • Day & Night (ICR), Digital Image Stabilization, Defog • IK08 	<ul style="list-style-type: none"> • 3MP @ 30fps • Wide Dynamic Range (120dB) • Simple focus, P-Iris • Day & Night (ICR), Digital Image Stabilization, Defog • IK10, IP66
SNF-7010/V/VM	2MP	SNB-6011	SNB-6010/6010A	SNB-H-6010
WiseNet III <p>IK10 IP66</p> <p>3MP Full HD 360° Fisheye</p> <ul style="list-style-type: none">• 1080p resolution w/ dewarped images• Wide Dynamic Range (120dB)• Panorama, quad, user selectable region• Analytics, bi-directional audio• IK10, IP66 (SNF-7010/VM)• M12 Connector (SNF-7010VM)		WiseNet III <p>2MP 2.4mm Covert</p> <ul style="list-style-type: none">• 1080p @ 30fps• Wide Dynamic Range (120dB)• Analog BNC output• Advanced motion detection, Defog• Multi-crop streaming• Extremely discreet design• Analytics• 134° Wide Angle View	WiseNet III <p>2MP 4.6mm Covert</p> <ul style="list-style-type: none">• 1080p @ 30fps• Wide Dynamic Range (120dB)• Advanced motion detection, Defog• Multi-crop streaming• Extremely discreet design• Analytics• Analog BNC Output (SNB-6010A)	WiseNet III <p>Height Marker w/2MP 4.6mm Covert</p> <ul style="list-style-type: none">• Fits most standard door frames• Durable steel construction• Highly visible color coded height levels• Curved surface w/180° HFOV camera adjustment• Wrap-around labels visible from side• 2MP 1080P camera installed

NETWORK

 <p>NEW SNB-J-6010</p> <p>WiseNet™ III</p> <p>Door Jamb Camera w/2MP 4.6mm Covert</p> <ul style="list-style-type: none"> • Designed for easy installation • Fits most standard door frames • Durable steel construction • Curved surface with 180° HFOV camera adjustment • 2MP 1080P camera installed 	 <p>NEW SNB-6005</p> <p>WiseNet™ III</p> <p>2MP Full HD Superior Low Light</p> <ul style="list-style-type: none"> • 1/1.9" PS 2.4M CMOS • 0.015Lux@F1.2(Color), 0.0015Lux F1.2(B/W) • Wide Dynamic Range (120dB) • Digital Image Stabilization • Smart compression • Multiple streaming • P-Iris, Simple focus (SNB-6004) • Analytics 	 <p>SNB-6004/6003</p> <p>WiseNet™ III</p> <p>2MP Full HD</p> <ul style="list-style-type: none"> • 1080p @ 60fps • Wide Dynamic Range (120dB) • Digital Image Stabilization • Smart compression • Multiple streaming • P-Iris, Simple focus (SNB-6004) • Analytics 	 <p>SNZ-6320</p> <p>WiseNet™ III</p> <p>2MP Full HD Zoom</p> <ul style="list-style-type: none"> • 1080p @ 60fps • 32x optical zoom • Multiple streaming • Analytics • Wide Dynamic Range (120dB) 	 <p>SNO-6084R</p> <p>WiseNet™ III</p> <p>IK10 IP66</p> <p>2MP Full HD Weatherproof IR</p> <ul style="list-style-type: none"> • 1080p @ 60fps • 2.8x simple focus • Wide Dynamic Range (120dB) • Digital Image Stabilization • Smart compression • Multiple streaming • Analytics • IP66, IK10
 <p>WiseNet™ III</p> <p>IP66</p> <p>2MP Full HD 1080p IR</p> <ul style="list-style-type: none"> • 1080p @ 30fps • 3.8mm fixed lens • Wide Dynamic Range (120dB) • Smart compression • Multiple streaming • Analytics • IP66 	 <p>WiseNet Lite</p> <p>IK10 IP66</p> <p>2MP Full HD Weatherproof IR</p> <ul style="list-style-type: none"> • 30fps@all resolutions (H.264) • 4.3x varifocal lens • Motion detection, Tampering • IR viewable length 65ft • Hallway view (Rotate 90°/270°) • Lens Distortion Correction • IK10, IP66 	 <p>WiseNet Lite</p> <p>IP66</p> <p>2MP Full HD Weatherproof IR</p> <ul style="list-style-type: none"> • 30fps@all resolutions (H.264) • 3.6mm fixed lens • Motion detection, Tampering • IR viewable length 65ft • Hallway view (Rotate 90°/270°) • Lens Distortion Correction • IP66 	 <p>WiseNet™ III</p> <p>2MP Full HD</p> <ul style="list-style-type: none"> • 1080p @ 60fps • 2.8x motorized lens (SND-6084) • Wide Dynamic Range (120dB) • Digital Image Stabilization • Smart compression • Multiple streaming • Analytics, Simple focus (SND-6084) 	 <p>SND-6084R</p> <p>WiseNet™ III</p> <p>2MP Full HD IR 1080p</p> <ul style="list-style-type: none"> • 1080p @ 60fps • 2.8x simple focus • Wide Dynamic Range (120dB) • Digital Image Stabilization • IR viewable length 49ft • Smart compression • Multiple streaming • Analytics
 <p>WiseNet™ III</p> <p>2MP Full HD 1080p</p> <ul style="list-style-type: none"> • 1080p @ 30fps • Built-in 3.8mm fixed lens • Wide Dynamic Range (120dB) • Digital Image Stabilization • Smart compression • Multiple streaming • Analytics 	 <p>WiseNet Lite</p> <p>2MP Full HD IR</p> <ul style="list-style-type: none"> • 30fps@all resolutions (H.264) • 4.3x varifocal lens • Motion detection, Tampering • IR viewable length 49ft • Hallway view (Rotate 90°/270°) • Lens Distortion Correction 	 <p>WiseNet Lite</p> <p>2MP Full HD IR</p> <ul style="list-style-type: none"> • 30fps@all resolutions (H.264) • 3.6mm fixed lens • Motion detection, Tampering • IR viewable length 65ft • Hallway view (Rotate 90°/270°) • Lens Distortion Correction 	 <p>WiseNet Lite</p> <p>2MP Full HD</p> <ul style="list-style-type: none"> • 30fps@all resolutions (H.264) • SND-L6012: 3.6mm fixed lens; SND-L6012: 2.8mm fixed lens • Motion detection, Tampering • Hallway view (Rotate 90°/270°) • Lens Distortion Correction 	 <p>NEW SNV-6085R</p> <p>WiseNet Lite</p> <p>IK10 IP66</p> <p>2MP Full HD Vandal-Resistant Network IR</p> <ul style="list-style-type: none"> • 60fps@all resolutions (H.264) • 2.8x simple focus • Wide Dynamic Range (120dB) • Digital Image Stabilization • Smart compression • Multiple streaming • Analytics • IK10, IP66
 <p>WiseNet™ III</p> <p>IK10 IP66</p> <p>2MP Full HD Vandal-Resistant/IR</p> <ul style="list-style-type: none"> • 1080p @ 60fps • 2.8x simple focus • Wide Dynamic Range (120dB) • Digital Image Stabilization • Smart compression • Multiple streaming • Analytics • IK10, IP66 	 <p>WiseNet Lite</p> <p>IK10 IP66</p> <p>2MP Full HD Vandal-Resistant Network IR</p> <ul style="list-style-type: none"> • 30fps@all resolutions (H.264) • 4.3x varifocal lens • Motion detection, Tampering • IR viewable length 65ft • Hallway view (Rotate 90°/270°) • Lens Distortion Correction 	 <p>WiseNet™ III</p> <p>IK10 IP66</p> <p>2MP Full HD Vandal-Resistant</p> <ul style="list-style-type: none"> • 1080p @ 60fps • Built-in 2.8mm fixed lens standard • Wide Dynamic Range (120dB) • Motion Detection, Audio Detection, Video Analytics • IP66, IK10 	 <p>WiseNet™ III</p> <p>IK10 IP66</p> <p>2MP Full HD Mobile Vandal-Resistant</p> <ul style="list-style-type: none"> • 1080p @ 60fps • 3mm fixed lens (103.1° view) standard • Wide Dynamic Range (120dB) • Motion Detection, Audio Detection, Video Analytics • IP66/IK10, M12, EN50155, EN50121 	 <p>NEW SNP-6321/6321H</p> <p>IK10 IP66</p> <p>2MP Full HD 32x Network PTZ</p> <ul style="list-style-type: none"> • H.264, MJPEG dual codec, Multiple streaming • Wide Dynamic Range (120dB) • Auto tracking, Analytics • PoE+, SD memory card, Bi-directional audio support • IP66/IK10 SNP-6320H, SNP-6320 + SHP-3701H
 <p>IK10 IP66</p> <p>2MP Full HD 32x Network PTZ</p> <ul style="list-style-type: none"> • H.264, MJPEG dual codec, Multiple streaming • Wide Dynamic Range (120dB) • Auto tracking, Analytics • PoE+, SD memory card, Bi-directional audio support • IP66/IK10 SNP-6320H, SNP-6320 + SHP-3701H 	 <p>IK10 IP66</p> <p>2MP Full HD 1080p 32x IR PTZ</p> <ul style="list-style-type: none"> • 1080p @ 60fps • 32x optical zoom • IR distance 493ft • Wide Dynamic Range (120dB) • Digital Image Stabilization • Auto Tracking • Multiple streaming • Analytics, IK10, IP66 	 <p>1.3MP</p>	 <p>WiseNet™ III</p> <p>1.3MP HD</p> <ul style="list-style-type: none"> • 1.3MP @60fps • Wide Dynamic Range (130dB) • Simple focus, P-iris • True Day & Night (ICR) • Digital Image Stabilization, Defog • Multi-crop streaming 	 <p>SNO-5084R</p> <p>WiseNet™ III</p> <p>IK10 IP66</p> <p>1.3MP Full HD Weatherproof IR</p> <ul style="list-style-type: none"> • 1.3MP @60fps • 2.8x simple focus • Wide Dynamic Range (130dB) • Intelligent Analytics • PoE+, SD memory card, Bi-directional audio support • IP66/IK10 SNP-6321H, SNP-6321 + SHP-3701H



SAMSUNG TECHWIN AMERICA

877-213-1222 • www.samsung-security.com

NETWORK



<p>SNO-L5083R</p>  <p>WiseNet Lite IK10 IP66</p> <p>1.3MP Full HD Weatherproof IR</p> <ul style="list-style-type: none"> • 30fps@all resolutions (H.264) • 4.3x varifocal lens • Motion detection, Tampering • IR viewable length 65ft • Hallway view (Rotate 90°/270°) • Lens Distortion Correction • IK10, IP66 	<p>SND-5084</p>  <p>WiseNet III</p> <p>1.3MP HD</p> <ul style="list-style-type: none"> • 1.3MP @ 60fps • 2.8x simple focus • Wide Dynamic Range (130dB) • Digital Image Stabilization • Smart compression • Multiple streaming • Analytics 	<p>SND-5084R</p>  <p>WiseNet III</p> <p>1.3MP HD IR</p> <ul style="list-style-type: none"> • 1.3MP @ 60fps • 2.8x simple focus • Wide Dynamic Range (130dB) • Digital Image Stabilization • Smart compression • Multiple streaming • Analytics • IR viewable length 98ft 	<p>SND-L5083R</p>  <p>WiseNet Lite</p> <p>1.3MP Full HD IR</p> <ul style="list-style-type: none"> • 30fps@all resolutions (H.264) • 4.3x varifocal lens • Motion detection, Tampering • IR viewable length 49ft • Hallway view (Rotate 90°/270°) • Lens Distortion Correction 	<p>SND-L5013</p>  <p>WiseNet Lite</p> <p>1.3MP Full HD</p> <ul style="list-style-type: none"> • 30fps@all resolutions (H.264) • 3.6mm fixed lens • Motion detection, tampering • Hallway view (Rotate 90°/270°) • Lens Distortion Correction
<p>SNV-5084/5084R</p>  <p>WiseNet Lite IK10 IP66</p> <p>1.3MP HD Vandal-Resistant/IR</p> <ul style="list-style-type: none"> • 1.3MP @ 60fps • 2.8x simple focus • Analytics • Day & Night (ICR), Wide Dynamic Range (130dB) • Simple focus, Enhanced DIS, Defog • Multi-crop streaming, PoE, IP66, IK10 • IR viewable length 98ft (SNV-5084R) 	<p>SNV-L5083R</p>  <p>WiseNet Lite IK10 IP66</p> <p>1.3MP Full HD Vandal-Resistant IR</p> <ul style="list-style-type: none"> • 30fps@all resolutions (H.264) • 4.3x varifocal lens • Motion detection, Tampering • IR viewable length 65ft • Hallway view (Rotate 90°/270°) • Lens Distortion Correction 	<p>SNP-5321/5321H</p>  <p>WiseNet III IK10 IP66</p> <p>1.3MP HD 43x PTZ</p> <ul style="list-style-type: none"> • H.264, MJPEG dual codec, Multiple streaming • Wide Dynamic Range (120dB) • Day & Night (ICR), Analytics • PoE+, SD memory card, Bi-directional audio support • IP66/IK10 SNP-5321H, SNP-5321 + SHP-3701H 	<p>SNP-5430/5430H</p>  <p>WiseNet Lite IK10 IP66</p> <p>1.3MP HD 720p 43x PTZ</p> <ul style="list-style-type: none"> • H.264, MJPEG dual codec, Multiple streaming • Day & Night (ICR), WDR (120dB) • Auto tracking, Analytics • PoE+, SD memory card, Bi-directional audio support • IP66/IK10 SNP-5430H, SNP-5430 + SHP-3701H 	<p>NVRs</p> 
<p>SRN-4000</p>  <p>64CH 400Mbps Premium</p> <ul style="list-style-type: none"> • Up to 64CH/400Mps 5MP Supported • Max 12 Hot-Swap HDDs (RAID 5/6) • HDMI/VGA local monitor • iSCSI Storage supported • Redundant Hot-Swap power supply • ONVIF Camera Compliant 	<p>SRN-1000</p>  <p>64CH 100Mbps</p> <ul style="list-style-type: none"> • 100Mbps recording bit rate • Max 5MP resolution support • Max 8 internal HDD • 2 external ports, supports expansion bay • RAID 5 support • ONVIF Camera Compliant 	<p>SRN-1673S</p>  <p>16CH with PoE+ Switch</p> <ul style="list-style-type: none"> • Up to 16CH 8MP supported • 80Mbps network camera recording • Plug & play by 16 PoE/PoE+ ports • Max 4HDDs, e-SATA storage supported • HDD removable (Easy install) • HDMI / VGA local monitor • ONVIF Camera Compliant 	<p>SRN-873S</p>  <p>8CH with PoE+ Switch</p> <ul style="list-style-type: none"> • Up to 8CH 8MP supported • 64Mbps network camera recording • Plug & play by 8 PoE/PoE+ ports • Max 2HDDs, e-SATA storage supported • HDMI / VGA local monitor • ONVIF Camera Compliant 	<p>SRN-473S</p>  <p>4CH with PoE+ Switch</p> <ul style="list-style-type: none"> • Up to 4CH 8M supported • 32Mbps network camera recording • Plug & play by 4 PoE/PoE+ ports • Max 1 HDD • HDMI / VGA local monitor • ONVIF Camera Compliant
<p>SRM-872</p>  <p>8CH Mobile</p> <ul style="list-style-type: none"> • Up to 8CH, 64Mbps recording • Plug & Play by 8 PoE Ports • 1 Hot - Swap HDD (2.5") • HDMI/VGA local monitor • GPS Supported • Standards Approval for Transportation 	<p>SRN-SENCMS-DSP</p>  <p>Central Video Mgmt Display</p> <ul style="list-style-type: none"> • Quad Core i7 4770 3.4GHz • GeForce GTX 660 2GB 2 Output • 8GB RAM, 1.0TB 7200rpm SATA Standard Hard Drive for System • Windows 7 Pro x64, 24x DVD-RW • Designed for SSM Console & VMS partner display module 	<p>SRN-SENCMS-DSPS</p>  <p>Central Video Mgmt Display Enterprise</p> <ul style="list-style-type: none"> • Quad Core i7 4770 3.4GHz • GeForce GTX 790 2GB 4 Output • 8GB RAM, 1.0TB 7200rpm SATA Standard Hard Drive for System • Windows 7 Pro x64, 24x DVD-RW • Designed for SSM Console & VMS partner display module 	<p>SRN-16SEN</p>  <p>16 Channel Storage Appliance</p> <ul style="list-style-type: none"> • 2U 16 Channel Video Storage Appliance set up for recording and client viewing • 4th generation Intel Dual Core i3 processor • Superior system performance independent 120GB SSD drive • Supports up to 4TB of raw storage • Designed for SSM-RS, license not included 	<p>SRN-SENCMS-CTL</p>  <p>Central Video Mgmt Server</p> <ul style="list-style-type: none"> • Manage multiple recording servers & cameras • Windows 2012 Server w/5 user • Intel Quad Core i7-4770 3.40GHz • 8GB DDR3, 500GB SATA HDD, 24x DVDRW • Desinged for SSM Media gateway or system manager
<p>SRN-SENCMS-CTL</p>  <p>Central Video Mgmt Server Enterprise</p> <ul style="list-style-type: none"> • Manage multiple recording servers & cameras • Windows 2012 Server w/5 user • Intel Quad Core Xeon E3 1220V3 3.1Ghz S1150 • 8GB DDR3, 1TB SATA HDD, 8x DVDRW • Designed for SSM Media gateway or system manager 	<p>SRN-32SEN</p>  <p>32 Channel Storage Appliance</p> <ul style="list-style-type: none"> • 2U 32 Channel Video Storage Appliance • 4th gen Intel Core i5 processor • Supports up to 12TB of raw storage 	<p>SRN-64SEN</p>  <p>64 Channel Storage Appliance</p> <ul style="list-style-type: none"> • 2U 64 Channel Video Storage Appliance • 3rd generation Intel Quad Core Xeon processor • Supports up to 12TB of raw storage 	<p>SRN-64SEN-RS</p>  <p>64 Channel Enterprise Storage Appliance</p> <ul style="list-style-type: none"> • 2U 64 Channel Video Storage Appliance • Intel Quad Core Xeon processor • Pr-configured Raid 5 • Redundant power supply standard • Available standard in 8, 12, 15, 24, 32, 40, 48, 96TB configurations 	<p>SPD-400</p>  <p>4CH Video Decoder</p> <ul style="list-style-type: none"> • H.264, MPEG-4, MJPEG decoding • Full HD (1080p) video output • Single and quad view • Sequence mode for multiple video sources



SAMSUNG TECHWIN AMERICA

877-213-1222 • www.samsung-security.com

NETWORK/ANALOG

SPE-400B	SPE-1600R	SPE-400/101/100	 Network Software	SmartViewer
				
4CH Encoder Blades <ul style="list-style-type: none">• 4CIF resolution @ 30fps• Multiple streaming simultaneously	16CH Video Encoder Rack <ul style="list-style-type: none">• 4CIF resolution @ 30fps• Multiple streaming simultaneously• 10/100/1000BASE-T• 4 slots	4CH / 1CH Video Encoder <ul style="list-style-type: none">• 4CIF @ 30fps• H.264, MPEG-4, MJPEG multiple codec• Multiple streaming simultaneously• 10/100/1000BASE-T: SPE-400 PoE, 10/100BASE-T: SPE-101/100• SD memory, bi-directional audio support: SPE-400/100	Central Management <ul style="list-style-type: none">• Simple management software for Samsung products• Up to 36 videos monitoring• Full screen mode, sequence mode• Up to 16 videos simultaneous playback• Supports H.265, H.264, MPEG-4, & MJPEG video formats	
				
Central Management <ul style="list-style-type: none">• Multi-site monitoring, Multi-client connection• Efficient alarm monitoring• Live & Map monitoring simultaneously• Multi-level group/user authority mgmt• Device Management, Search/ Playback	<ul style="list-style-type: none">• Real-time event log message• Various system actions for events from devices• Multi-site monitoring / multi-client• Central management software for Samsung products• Live/map viewer	SSM Virtual Matrix Add on module for SSM <ul style="list-style-type: none">• Monitor layout (4:3, 16:9, full screen mode -100 channel) supported• Split layout supported• Wall OSD On/Off supported• Event salvo switching• Controls 16/36 monitors (VM10L/20L)• VM00: free for SPD-400	Samsung Recording Server <ul style="list-style-type: none">• Works with SSM• RS00: 16CH free• RS10/20/30: 36CH/72CH/128CH• 400Mbps Recording Throughput• ONVIF compatible (only on SSM-RS10/20/30)	Mobile Client for SSM <ul style="list-style-type: none">• View Layout/Device list by user• View live streaming video with PTZ control• H.264/MJPEG• Video Image Flip / Mirror, Video Image Capture• Quick & easy access at mobile, WiFi networks
			 BEYOND IK10 IP66 1280H Wide Dynamic Range Weatherproof IR <ul style="list-style-type: none">• 1,000TV Lines High Resolution• 0.03Lux@F1.2, 50IRE, 0.01Lux@ F1.2, 30IRE• SCB-5003/5005: Wide Dynamic Range (120dB)• Samsung Super Dynamic Range, Defog• Simple focus (SCB-5005)• Coaxial communication	 BEYOND 1280H Wide Dynamic Range <ul style="list-style-type: none">• 1000TV lines high resolution• SCD-5083: Wide Dynamic Range (120dB)• Samsung Super Dynamic Range, Samsung Super Noise Reduction IV, Defog• Coaxial Communication• IP66, IK10
 BEYOND 1280H <ul style="list-style-type: none">• 1000TV lines high resolution• Samsung Super Dynamic Range, Samsung Super Noise Reduction IV, Defog• Coaxial communication	 BEYOND 1280H Wide Dynamic Range IR <ul style="list-style-type: none">• 1,000TV Lines High Resolution• 0.03Lux@F1.2, 50IRE (Color), 0.01Lux@F1.2, 30IRE (Color), 0Lux (IR LED on) (B/W)• 2.8x varifocal Lens• Wide Dynamic Range (120dB), Day & Night (ICR)• Coaxial Communication	 BEYOND IK10 IP66 1280H Wide Dynamic Range <ul style="list-style-type: none">• 1000TV lines high resolution• 0.03Lux@F1.2, 50IRE (Color), 0.01Lux@F1.2, 30IRE (Color), 0Lux (IR LED on) (B/W)• 2.8x simple focus• Wide Dynamic Range (120dB), Day & Night (ICR)• Coaxial Communication• IP66, IK10	 BEYOND IK10 IP66 1280H Wide Dynamic Range <ul style="list-style-type: none">• 1000TV lines high resolution• SCV-5083: Wide Dynamic Range (120dB)• Samsung Super Dynamic Range, Samsung Super Noise Reduction IV, Defog• Coaxial communication• IP66, IK10	 BEYOND IK10 IP66 1280H Wide Dynamic Range Vandal-Resistant IR <ul style="list-style-type: none">• 1,000TV Lines High Resolution• 0.03Lux@F1.2, 50IRE (Color), 0.01Lux@F1.2, 30IRE (Color), 0Lux (IR LED on) (B/W)• 2.8x varifocal Lens• Wide Dynamic Range (120dB)• Defog, Samsung Super Dynamic Range• IP66, IK10
	 700TV/650TV Lines <ul style="list-style-type: none">• 700TVL (Color), 700TVL (B/W); SCB-3003• 650TVL (Color), 700TVL (B/W); SCB-3001• 0.1Lux@F1.2 (Color), 0.01Lux (B/W)• Wide Dynamic Range, Virtual Progressive Scan, Day & Night (ICR), Intelligent video• Simple Focus : SCB-3003• Coaxial control	 680TV Lines, 37x Zoom <ul style="list-style-type: none">• 680TVL (Color)• Min. 0.2Lux @ F1.6 (Color), 0.01Lux (B/W)• Pelco-C (Coaxitron), RS-485	 680TV Lines, 27x Zoom <ul style="list-style-type: none">• 680TVL (Color)• Min. 0.2Lux @ F1.6 (Color), 0.01Lux (B/W)• Pelco-C (Coaxitron), RS-485	 700TV Lines <ul style="list-style-type: none">• 960H• 700TVL (Color)• Min. 0.1Lux@F1.2 (Color), 0.01Lux (B/W)• 3.6x simple focus• Wide Dynamic Range• Analytics• Coax : Pelco-C (Coaxitron)

ANALOG

SCD-2082 	SCD-2042R/2022R 	SCD-2021R 	SCV-3083 	SCP-2373/2373H 
700TV Lines <ul style="list-style-type: none"> • 700TVL (Color), 650TVL (B/W) • Min. 0.1Lu @ F1.2 (Color) • 3.6x (2.8 ~10mm) varifocal lens; • Motion detection • Coax : Pelco-C (Coaxitron) 	700TV Lines IR <ul style="list-style-type: none"> • 700TVL (Color) • IR distance 23ft • SCD-2022R: 3.8mm fixed lens; • SCD-2042R: 8mm fixed lens • Motion Detection • Coax control 	650TV Lines, Compact IR <ul style="list-style-type: none"> • 650TVL (Color) • IR distance 66ft • 3.6mm fixed lens • Coax control 	IP66 700TV Lines, Vandal-Resistant <ul style="list-style-type: none"> • 700TVL (Color), 700TVL (B/W) • Min. 0.1Lux@F1.2 (Color), 0.01Lux (B/W) • 3.6x simple focus • Virtual Progressive Scan, Day & Night (ICR), Analytics • IP66, Samsung Super Noise ReductionIII, Coaxial control 	IP66 680TV Lines, 37x PTZ <ul style="list-style-type: none"> • 680TVL (Color), 700TVL (B/W) • Min. 0.2Lux@F1.6 (Color), 0.02Lux (B/W) • Day & Night (ICR), Samsung Super Noise ReductionIII • IP66, Coaxial control
SCP-2273/2273H  IP66 680TV Lines, 27x PTZ <ul style="list-style-type: none"> • 680TVL (Color), 700TVL (B/W) • Min. 0.2Lux@F1.6 (Color), 0.02Lux (B/W) • 27x zoom, digital 16x • Day & Night (ICR), Samsung Super Noise ReductionIII • IP66, Coaxial control 	D1 	SCZ-3430 	SCZ-3250/2250 	SCO-2040R  IP66 650TV Lines, Compact IR <ul style="list-style-type: none"> • 650TVL (Color) • 0Lux (IR LED on) • Built-in fixed lens 8mm • Motion Detection, Samsung Super Noise ReductionIII, Defog, Coaxial control • Day & Night (ICR), IP66
SCO-2080  IP66 600TV Lines <ul style="list-style-type: none"> • 600TVL (Color), 700TVL (B/W) • Min. 0.15Lux @ F1.2(Color), 0.001Lux (B/W) • 3.6x (2.8 ~10mm) varifocal lens • Pelco-C (Coaxitron), RS-485 • IP66 	SCO-2080R  IP66 600TV Lines, IR <ul style="list-style-type: none"> • 600TVL (Color), 700TVL (B/W) • IR distance 164ft • 3.6x (2.8~10mm) varifocal lens • Motion detection • Coax : Pelco-C (Coaxitron), RS-485 • IP66 	SCO-2080R/2080RH 	SCO-2120R  IP66 600TV Lines, 12x Zoom, IR <ul style="list-style-type: none"> • 600TVL (Color), 700TVL (B/W) • IR distance 230ft • Analytics • Coax : Pelco-C (Coaxitron), RS-485 • IP66 	SCD-3080/2080  600TV Lines <ul style="list-style-type: none"> • 600TVL (Color), 700TVL (B/W) • SCD-3080: Min. 0.3Lux @ F1.2 (Color), 0.01Lux (B/W); SCD-2080: Min. 0.15Lux @ F1.2 (Color), 0.001Lux (B/W) • 3.9x (2.8 ~11mm)/3.6x (2.8 ~10mm) varifocal lens • Wide Dynamic Range (SCD-3080) • Coax : Pelco-C (Coaxitron)
SCD-2080E/2060E 	SCD-2010 	SCD-2010F 	SCD-1020R  IP66 High Resolution Weatherproof IR <ul style="list-style-type: none"> • 600TV lines (Color), 700TV lines (B/W) • Min. illumination 0Lux(IR LED On), IR distance 50m • 3.6x Varifocal lens (2.8~10mm) • Day&Night(ICR), Motion Detection, Samsung Super Noise Reduction III • IP66, Coax : Pelco-C (Coaxitron) 	SCV-3080  IP66 High Resolution Vandal-Resistant Dome <ul style="list-style-type: none"> • High resolution of 600TV lines (Color), 700TV lines (B/W) • Min. illumination 0.3Lux@F1.2 (Color), 0.01Lux (B/W) • 3.9x V/F lens (2.8 ~ 11mm), Wide Dynamic Range,, True Day / Night (ICR) • IP66, Coaxial control (Pelco-C)
SCV-2080R  IK10 IP66 600TV Lines, Vandal IR <ul style="list-style-type: none"> • 600TVL (Color), 700TVL (B/W) • IR distance: 98ft • 3.6x (2.8~10mm) varifocal lens • Motion Detection • Coax : Pelco-C (Coaxitron) • IK10, IP66 	SCP-3430H  IK10 IP66 600TV Lines, 43x PTZ <ul style="list-style-type: none"> • 600TVL (Color), 700TVLs (B/W) • Min. 0.7Lux @ F1.65 (Color), 0.07Lux (B/W); • Wide Dynamic Range • Analytics • Pelco-C (Coaxitron), RS-485/422 • IP66, IK10 	SCP-3371 	SCP-3370TH  IK10 IP66 600TV Lines, 37x PTZ <ul style="list-style-type: none"> • 600TVL (Color), 700TVL (B/W) • Min. 0.7Lux @ F1.6 (Color), 0.07Lux (B/W) • Wide Dynamic Range • Analytics, Auto-tracking • Pelco-C (Coaxitron), RS-485/422 • IK10, IP66 	SCP-3120/3120VH  IK10 IP66 600TV Lines, 12x PTZ <ul style="list-style-type: none"> • 600TVL (Color), 700TVL (B/W) • Min. 0.7Lux @ F1.65 (Color), 0.07Lux (B/W) • Wide Dynamic Range • Analytics • RS-485 • Heater • IK10, IP66 : SCP-3120VH



ANALOG

SCP-2120 	SCP-2370RH  IK10 IP66	SCU-2370  IP66	DVRs	SRD-1680D 
600TV Lines, 12x PTZ <ul style="list-style-type: none">• 600TVL (Color), 700TVL (B/W)• Min. 0.2Lux @ F1.6 (Color), 0.004Lux (B/W)• Motion detection• Pelco-C (Coaxitron), RS-485	600TV Lines, 37x IR PTZ <ul style="list-style-type: none">• 600TVL (Color), 700TVL (B/W)• IR Distance 328ft• Motion Detection• Pelco-C (Coaxitron), RS-485/422• Smart IR• IK10, IP66	600TV Lines, 37x PTZ <ul style="list-style-type: none">• 600TVL (Color), 700TVL (B/W)• Min. 0.2Lux @ F1.6 (Color), 0.02Lux (B/W)• 37x• Motion Detection• IP66• Pelco-C (Coaxitron), RS-485		8CH Full HD/16CH 960H Coaxial Hybrid <ul style="list-style-type: none">• 16CH 700TV lines / 8CH Full HD 1080p real-time recording• Full HD, VGA/HDMI video output• Max. 4 internal HDDs• HDD removable (Easy install)• Smart searching, Tampering support• PTZ Control via Coaxial Cable• Up to 64Mbps network bandwidth
SRD-1676D 	SRD-1656D 	SRD-1654D 	SRD-1642 	SRD-880D 
16CH 1280H Real-time Coaxial <ul style="list-style-type: none">• Up to 480fps recording rate• Video Loophthrough• Max. 4 internal HDDs• Set independently for each channel - REC/Quality/Resolution• Digital Video Spot(2EA), USB(2ports) backup	16CH CIF Real-time Coaxial <ul style="list-style-type: none">• Max. 4 internal HDDs• Video Loophthrough• Up to 480fps recording rate• 16CH 1280H real-time DVR• Digital Video Spot(2EA), USB(2ports) backup	16CH CIF Real-time <ul style="list-style-type: none">• Up to 480fps recording rate• Max. 4 internal HDDs• PTZ control via Coax cable• 4CH audio inputs / 1CH audio output• DVD-RW• Smart phone support• Full HD 1080p video out via HDMI	16CH 960H Real-time Coaxial <ul style="list-style-type: none">• Up to 480fps recording rate• Easy user interface, common across all Samsung DVRs - GUI / Search / Back up / Set-up• Set independently for each channel• Privacy mask support each channel	8CH Full HD-SDI <ul style="list-style-type: none">• Up to 240fps recording rate• Touch interface front panel• Max. 4 internal HDDs• DVD-RW, Smart phone support• PTZ Control via Coaxial Cable• Up to 64Mbps network bandwidth
SRD-876D 	SRD-873D 	SRD-854D 	SRD-850DC 	SRD-842 
8CH 1280H H.264 <ul style="list-style-type: none">• 8CH 1280H real-time DVR• Video Loophthrough• Up to 240fps recording rate• Max. 4 internal HDDs• Set independently for each channel - REC/Quality/Resolution• Digital Video Spot(2EA), USB(2ports)	8CH 960H/D1 Real-time Coaxial <ul style="list-style-type: none">• Up to 240fps recording rate• Max. 4 internal HDDs• PTZ control via Coax cable• 8CH audio inputs / 1CH audio output• DVD-RW• Smart phone support	8CH CIF Real-time <ul style="list-style-type: none">• Up to 240fps recording rate• Max. 4 internal HDDs• PTZ control via Coax cable• Full HD 1080p video out via HDMI• 4CH audio inputs / 1CH audio output• DVD-RW• Smart phone support• Touch interface front panel	8CH CIF Real-time Coaxial <ul style="list-style-type: none">• Up to 240fps recording rate• Max. 5 internal HDDs• PTZ control via Coax cable• 8CH audio inputs / 1CH audio output• DVD-RW• Smart phone support	8CH 960H Real-time Coaxial <ul style="list-style-type: none">• Up to 480fps recording rate• Easy user interface, common across all Samsung DVRs - GUI / Search / Back up / Set-up• Set independently for each channel - REC / Quality / Resolution• Privacy mask support each channel• Smart phone support
SRD-840 	SRD-476D 	SRD-473D 	SRD-470D 	SRD-445 
8CH CIF Real-time H.264 <ul style="list-style-type: none">• Up to 240 (NTSC) fps recording rate• Internal Max. HDD x 1• Compact product footprint :• Smart phone support	4CH 960H Real-time Coaxial <ul style="list-style-type: none">• 4CH 1280H real-time DVR• Video Loophthrough• Up to 120fps recording rate• Max. 1 internal HDDs• Video Spot(analog 1EA, Digital 1EA), USB(2ports) backup	4CH 960H Real-time Coaxial <ul style="list-style-type: none">• Max. resolution of 960 x 480 / 960 x 576• Coaxitron support• Smart phone support (Android / iOS)• Full HD 1080p video out via HDMI• Smart searching, Tampering detection• Enhanced Network Bandwidth up to 32Mbps• Smart phone support	4CH 4CIF Real-time H.264 <ul style="list-style-type: none">• 4CIF resolution real-time recording capability• SATA I/F HDD support (Internal Max. HDD x 1)• DVD-RW• Smart phone support	4CH 960H Coaxial <ul style="list-style-type: none">• 4CH 960H• Up to 120fps recording rate• Max. 1 internal HDDs• Set independently for each channel - REC/Quality/Resolution• Smart phone support
SRD-443 	SRD-440 	SVS-5R/5E 	Controllers	SPC-2000 
4CH CIF Real-time Compact Design <ul style="list-style-type: none">• CIF resolution real-time recording capability• Max resolution 4 CIF (720 x 480 NTSC)• 2 USB ports (Rear)• Event flash storage• Smart phone (iOS and Android) support	4CH CIF Real-time CIF H.264 <ul style="list-style-type: none">• 4CH CIF real-time DVR• CIF resolution real-time recording capability (4CIF recording available)• SATA I/F HDD support (Internal Max. HDD x 1)• Smart phone support	RAID 5 Unit /HDD Extension Unit <ul style="list-style-type: none">• 1U 19-inch rack case• Data transmission speed : Up to 3.0Gbps (SATA II)• Available SATA HDD : Up to 4TB		Controller <ul style="list-style-type: none">• Superior system compatibility• 3D joystick control• Quick and easy installation• Supports SSM, SmartViewer, NVRs, Net-i viewer



SAMSUNG TECHWIN AMERICA

877-213-1222 • www.samsung-security.com

OTHER PRODUCTS

 <p>SPC-6000</p> <p>System Control Keyboard</p> <ul style="list-style-type: none"> • 5" TFT touch LCD • Control PTZ dome cameras, DVRs and matrix switchers • Up to 255 units with a single controller • Connect to a system up to 16 controllers 	 <p>SPC-2010</p> <p>PTZ/DVR System</p> <ul style="list-style-type: none"> • Control up to 255 PTZ cameras/DVRs • Built-in 3 axis twist joystick • Built-in Jog shuttle • 16 x 2 Character LCD display • RS-485 and RS-422 interface • Supports SSM, SmartViewer, NET-I viewer & NVRs 	 <p>SPC-1010</p> <p>PTZ Control Keyboard</p> <ul style="list-style-type: none"> • Control up to 255 PTZ cameras • Multi protocols supports • OSD Menu, 3D joystick control • RS-485 and RS-422 interface 	 <p>SPC-300</p> <p>Coaxial Remote</p> <ul style="list-style-type: none"> • Control via coaxial cable or RS-485 • Camera connected : 1unit • Cable extension : max. 500m (with 5C-2V cable) • RS-485 and RS-232C interface 	 <p>SPC-200</p> <p>Camera Zoom & OSD</p> <ul style="list-style-type: none"> • Camera zoom in/out, OSD control • RS-485 communication • Zoom camera RJ-45 connector control
<h2>Monitors</h2>	 <p>SMT-4032</p> <p>40" LED Monitor</p> <ul style="list-style-type: none"> • Support up to 1920 x 1080 resolution • Fast response time 8ms • High contrast ratio 5000 : 1 • Excellent picture quality with LED back light • Video Input : HDMI/VGA/Component (common) 	 <p>SMT-3232</p> <p>32" LED Monitor</p> <ul style="list-style-type: none"> • Support up to 1920 x 1080 resolution • Fast response time 8ms • High contrast ratio 5000 : 1 • Excellent picture quality with LED back light • Video Input : HDMI/VGA/Component (common) 	 <p>SMT-2730</p> <p>27" LED Monitor</p> <ul style="list-style-type: none"> • Support up to 1920 x 1080 resolution • Contrast ratio 1,000 : 1 • Excellent picture quality with LED back light • Video output : HDMI, VGA, Composite 	 <p>SMT-2232</p> <p>21.5" Wide LED Monitor</p> <ul style="list-style-type: none"> • Support up to 1920 x 1080 resolution • High contrast ratio 1000 : 1 • Fast response time 5ms • 120Hz motion technology
 <p>SMT-1934</p> <p>19" LED Monitor</p> <ul style="list-style-type: none"> • Support up to 1280 x 1024 resolution • High contrast ratio 1000 : 1 • Fast response time 5ms • Video output : HDMI, VGA, Composite 	 <p>SMT-1930</p> <p>18.5" Wide LED Monitor</p> <ul style="list-style-type: none"> • Support up to 1366 x 768 resolution • High contrast ratio 1,000 : 1 • Fast response time 5ms • 120Hz motion technology 	 <p>SMT-1914</p> <p>19" LED Monitor</p> <ul style="list-style-type: none"> • Support up to 1280 x 1024 resolution • High contrast ratio 1000 : 1 • Fast response time 5ms • Video output : VGA 	 <p>SMT-1734</p> <p>17" LED Monitor</p> <ul style="list-style-type: none"> • Support up to 1,280 x 1,024 resolution • High contrast ratio 1,000 : 1 • Fast response time 5ms • Video input : HDMI, VGA, BNC • Tempered glass screen 	<h2>Others</h2>
 <p>SLA-E-M1240DN</p> <p>6MP Day/Night Varifocal 1/2"</p> <ul style="list-style-type: none"> • Design for 6MP CS mount surveillance box camera • Full glass optical composition with metal body • 12-40mm /F1.8 • IR Corrected • DC Auto Iris 	 <p>SLA-F-M419DN</p> <p>6MP Day/Night Varifocal 1/1.8"</p> <ul style="list-style-type: none"> • Design for 6MP CS mount surveillance box camera • Superior low light performance • 4.1-9mm /F1.6 • IR Corrected • DC Auto Iris 	 <p>SLA-F-M1550DN</p> <p>3MP Day/Night Varifocal 1/2.7"</p> <ul style="list-style-type: none"> • f15-50mm / F1.5 • F1.0/F1.3/F1.3 DC type auto iris • Auto Iris (DC type) • ND Filter • Aspherical Lens • RoHS Compliant 	 <p>SLA-F-M226DN</p> <p>3MP Day/Night Varifocal 1/2.7"</p> <ul style="list-style-type: none"> • SLA-F-M226DN: f2.2-6mm / F1.3 • F1.0/F1.3/F1.3 DC type auto iris • Auto Iris (DC type) • ND Filter • Aspherical Lens • RoHS Compliant 	 <p>SLA-M-M21D</p> <p>Megapixel Fixed Lens</p> <ul style="list-style-type: none"> • Super wide angle f2.1mm • High quality megapixel resolution • Easy to install • Compatible with SNV-6013, sSNV-6012M
 <p>SLA-3580DN/2812DN</p> <p>CS-mount Auto Iris Lens</p> <ul style="list-style-type: none"> • F1.0/F1.4/F1.3/F1.6 DC Type auto iris • Varifocal lens : (SLA-3580DN: 3.5 ~ 8mm / 0.14" ~ 0.31"; SLA-2812DN: 2.8 ~ 12mm / 0.11" ~ 0.47" 	 <p>SLA-M2890DN/2890PN</p> <p>1/2.8" CS-mount Auto Iris Megapixel Lens</p> <ul style="list-style-type: none"> • F1.2 DC & P-Iris type auto iris • Varifocal lens: 2.8 ~ 9mm / 0.11" ~ 0.35" 	 <p>SLA-M3180PN</p> <p>CS-mount Auto Iris Megapixel</p> <ul style="list-style-type: none"> • F1.4/F1.2 DC type auto iris • Varifocal lens : 3.1 ~ 8mm / 0.12" ~ 0.31" • P-Iris 	 <p>PWR-P-POE15</p> <p>15.4W PoE Single Port Injector</p> <ul style="list-style-type: none"> • Up to 15.4W - IEEE802.3af - 1 Gigabit • Supports 10/100/1000M Base-T Applications • Input: AC100-240V, 50/60Hz • Output: 54VDC, .03A • CE / FCC Compliant 	 <p>PWR-P-POE30</p> <p>30W PoE+ Single Port Injector</p> <ul style="list-style-type: none"> • Up to 30W - IEEE802.3at - 1 Gigabit • Supports 10/100/1000M Base-T Applications • Input: AC100-240V, 50/60Hz • Output: 54VDC, .06A • CE / FCC Compliant

